

# 4MP Fixed-focal Wi-Fi Battery Bullet Network Camera

## DH-BF4CA-XL



#### **Series Overview**

Driven by industry-leading technology, Dahua Wireless Series network cameras are highly precise and easy to install, producing high-quality images. They have strong wireless connection capabilities and do not require network cables, eliminating the need for a professional construction team. This series of cost-effective cameras supports local storage and is dustproof and waterproof. It is ideal for small and medium-sized scenes such as retail stores, homes, and other small and medium-sized enterprises.



#### 4MP

Clear images with sharp details



#### AOV (Always-On Video) Mode

24/7 protection with all-day recording and ultra-low power consumption



#### **Dual-Band Wi-Fi 6**

The perfect integration of speed and anti-interference.



#### H.265

Advanced H.265 compression technology



#### Long-lasting Power, Non-stop Protection

Uninterrupted operations through battery and solar charging



#### **Sound and Light Alarm**

Provides instant alarms to deter



#### **Bluetooth Pairing**

Fast pairing with Bluetooth



#### **DMSS App**

Easy to use



### Al Precise Detection with Quick Wake Up

Accurate human and vehicle detection with instant alerts



#### **Smart Dual Light**

Captures color details for post-event



#### **Supports Micro SD Card**

Low-cost storage



#### **IP66 Protection**

Withstands harsh environments



## **Upgrade Your Experience with DMSS**

Intuitive AloT app for individual security



#### **Remote Management**

Live view and recording history



#### **Notifications and Alerts**

Accurate and timely



#### **Easy sharing**

Safer device sharing with family and friends



#### **High Security**

Stay secure with all data encrypted











## **Specifications**

#### Camera

Image Sensor 1/3" CMOS

Max. Resolution 2560 (H) × 1440 (V)

Up to 15 m (49.21 ft) (IR) Up to 20 m (65.62 ft) (Warm light) Illumination Distance

Illuminator Number 2 (Multi-core (IR + warm) light)

Angle Adjustment

Tilt: -60° to 0° Rotation: 0° to 360°

12 m (the height of device is 2.5 m, placed PIR Sensor Distance

8 m (the height of the device is 2 m, placed at an angle of 30° from the horizontal)

Fixed-focal Lens Type Focal Length 2.1 mm Max. Aperture F1.6

Field of View H: 122.5°; V: 66°; D: 144.5°

**Intelligence** 

Human Detection Yes Vehicle Detection Yes

**Audio and Video** 

Video Compression H.265

Main stream: 2560 × 1440@(1–15 fps) Sub stream: 640 × 360@(1–15 fps) \*The values above are the max, frame rates of each

Video Frame Rate stream; for multiple streams, the values will be subjected to the total encoding capacity.

Video Bit Rate H.265: 32 kbps-4096 kbps Day/Night Auto(ICR)/Color/B/W

WDR

Motion Detection OFF/ON (4 areas, rectangular)

Built-in MIC Yes, built-in Mic Built-in Speaker Yes, built-in speaker

G.711a; G.711Mu; PCM Audio Compression

#### **Network**

IEEE 802.11a/b/g/n/ac/ax 2.412−2.472 GHz, 2.4 G, EIRP≤20 dBm & 5.15−5.25 GHz, 5 G, EIRP≤23 Wi-Fi

dBm@5150-5250 MHz

Wi-Fi Pairing Bluetooth pairing

Micro SD card (support max. 512 GB) Storage

Management Software DMSS

Mobile Client Android:iOS

**General** 

CE-LVD: EN62368-1;

CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU; Certifications

CE-RED: Radio Equipment Directive 2014/53/EU

**Power Supply** USB (5 VDC±5%, 2 A)

Ultra power saving mode: 0.008 W Power saving mode: 0.008 W Power Consumption

AOV mode: 0.2 W Performance mode: 1.22 W

Operating Temperature -20 °C to +60 °C (-4 °F to +140 °F)

Operating Humidity ≤95% (RH), non-condensing

Protection IP66

Reset Button; Power Button Camera Button

Casing Material

Product Dimensions 186.5 mm × Φ65.0 mm (7.34" × Φ2.56")

Net Weight 0.37 kg (0.82 lb)

**Battery** 

**Battery Capacity** 32.4 Wh

## What's in the box



Position Map  $\times$  1

Screw Package × 1 Bracket × 1

Quick Start Guide  $\times$  1

Power Cable × 1

Legal and regulation information × 1



