



Wall-Mounted Enclosures

A proper housing for your IT equipments



MARSRIVA Technology Co., Ltd.

www.marsriva.com

Features

1. Design Features

- Excellent air ventilation design for optimal airflow.
- Toughened glass front door with a secure key lock.
- Multiple cable accesses for convenient wiring and maintenance.

2. Structural Design

- Removable side panels with easy-to-use handy latches.
- Wall-mountable or desktop standalone with versatile installation options.
- Available in both single and double sections to meet diverse needs.

3. Adjustability and Options

- Adjustable mounting profile to accommodate different equipment and requirements.
- Height-selectable for customizable configurations.

4. Material and Coating

- Constructed with SPCC high-quality cold-rolled steel for robust support.
- Tough textured powder coat finish for enhanced durability.

5. Security and Protection

- Equipped with an IP20 protection grade for basic equipment protection.
- Front door with a key lock for added security.



Specification

Material	SPCC Cold Rolled Steel
Thickness	Mount Profile: 1.5mm
	Side Panel: 0.8mm
	Others: 1.2mm
Tempered Glass Thickness	5mm
Surface Finish	Degreasing, Phosphoric, Powder Coated
Loading Capacity	60kg
Degree of Protection	IP20
Color	Black
Standard	DIN41494 part 1 and part 7
	ANSI/EIARS-310-E
	RoHS / IEC297-2 / ETSI



Ordering Information

Model	Width (mm)	Depth (mm)	Height (mm)	Capacity (U)
WS6404	600	450	280	4
WS6406	600	450	370	6
WS6409	600	450	500	9
WS6412	600	450	635	12
WS6415	600	450	770	15
WS6418	600	450	900	18
WS6422	600	450	1080	22
WS6604	600	600	280	4
WS6606	600	600	370	6
WS6609	600	600	500	9
WS6612	600	600	635	12
WS6615	600	600	770	15
WS6618	600	600	900	18
WS6622	600	600	1080	22

Features

- 1. Design Features**
 - Excellent air ventilation design for optimal airflow.
 - Toughened glass front door with a secure key lock.
 - Multiple cable accesses for convenient wiring and maintenance.
- 2. Structural Design**
 - Removable side panels with easy-to-use handy latches.
 - Wall-mountable or desktop standalone with versatile installation options.
 - Available in both single and double sections to meet diverse needs.
- 3. Adjustability and Options**
 - Adjustable mounting profile to accommodate different equipment and requirements.
 - Height-selectable for customizable configurations.
- 4. Material and Coating**
 - Constructed with SPCC high-quality cold-rolled steel for robust support.
 - Tough textured powder coat finish for enhanced durability.
- 5. Security and Protection**
 - Equipped with an IP20 protection grade for basic equipment protection.
 - Front door with a key lock for added security.



Specification

Material	SPCC Cold Rolled Steel
Thickness	Mount Profile: 1.5mm
	Side Panel: 0.8mm
	Others: 1.2mm
Tempered Glass Thickness	5mm
Surface Finish	Degreasing, Phosphoric, Powder Coated
Loading Capacity	60kg
Degree of Protection	IP20
Color	Black
Standard	DIN41494 part 1 and part 7
	ANSIEIARS-310-E
	RoHS / IEC297-2 / ETSI



Ordering Information

Model	Width (mm)	Depth (mm)	Height (mm)	Capacity (U)
WD6404	600	550	280	4
WD6406	600	550	370	6
WD6409	600	550	500	9
WD6412	600	550	635	12
WD6415	600	550	770	15
WD6418	600	550	900	18
WD6422	600	550	1080	22
WD6604	600	600	280	4
WD6606	600	600	370	6
WD6609	600	600	500	9
WD6612	600	600	635	12
WD6615	600	600	770	15
WD6618	600	600	900	18
WD6622	600	600	1080	22



6409: 600mm*450mm*9U



6609: 600mm*600mm*9U



6412: 600mm*450mm*12U



6612: 600mm*600mm*12U



6415: 600mm*450mm*15U



6615: 600mm*600mm*15U