

EC-PC4UD55B-XXX-GY-10

NETLAN U/UTP
 4 , .5e (D), 100 , 2 RJ45/8P8C,
 T568B, , CCA, - 10 .

✓	-1	/
✓		
✓		

(-)

EC-PC4UE55B-XXX-GY-10

5 ,
 T568B.

RJ45/8P8C.

NETLAN



	EC-PC4UD55B-XXX-GY-10
	5e
	100
	UTP
	4
	CCA
	26 AWG (7 0,160 ± 0,1)
	2xRJ45/8P8C
	3
	T568B
	(PE)
	PVC
	5,5 ± 0,3
	: ISO/IEC 11801, EN 50173 TIA/EIA-568
	10BASE-T, 100BASE-TX, 100BASE-T4, 1000BASE-T, ATM-25, ATM-51, ATM-155, 100VG-AnyLan, TR-4, TR-16 Active, TR-16 Passive
	- -20 +60. - -20 +50
	1
	10

					C ₃	
EC-PC4UD55B-005-GY-10	5e		0,5	10	0,001125	0,200
EC-PC4UD55B-010-GY-10	5e		1	10	0,002040	0,280
EC-PC4UD55B-015-GY-10	5e		1,5	10	0,001680	0,370
EC-PC4UD55B-020-GY-10	5e		2	10	0,003094	0,460
EC-PC4UD55B-030-GY-10	5e		3	10	0,003248	0,620
EC-PC4UD55B-050-GY-10	5e		5	10	0,004900	0,970
EC-PC4UD55B-100-GY-10	5e		10	10	0,012600	1,990